

## CLOCE CIRCUIT SYSTEM

MODEL	EL 1.5CA	EL 1.8CA	EL 2.0CA	EL 2.5CA
DIMENSIONS (mm)	1490x990x85	1490x1225x85	1990x990x85	1990x1225x85
	FULL PLATE SELECTIVE SURFACE			
ABSORBER TYPE	ALUMINIUM WITH LASER	ALUMINIUM WITH LASER	ALUMINIUM WITH LASER	ALUMINIUM WITH LASER
	WELDING	WELDING	WELDING	WELDING
HORIZONTAL TUBES TYPE	COPPER TUBES Φ22	COPPER TUBES Φ22	COPPER TUBES Φ22	COPPER TUBES Φ22
VERTICAL TUBES TYPE	COPPER TUBES Φ8	COPPER TUBES Φ8	COPPER TUBES Φ8	COPPER TUBES Φ8
CASING	ANODIZED ALUMINIUM PROFILE	ANODIZED ALUMINIUM PROFILE	ANODIZED ALUMINIUM PROFILE	ANODIZED ALUMINIUM PROFILE
GROSS AREA	1.47m²	1.82m²	1.97m²	2.43m <sup>2</sup>
WEIGHT (kg)	21	27	30	38
CAPACITY (L)	1.18	1.34	1.35	1.70
BACK INSULATION	GLASS WOOL 60mm	GLASS WOOL 60mm	GLASS WOOL 60mm	GLASS WOOL 60mm
SIDE INSULATION	GLASS WOOL 30mm	GLASS WOOL 30mm	GLASS WOOL 30mm	GLASS WOOL 30mm
GLASS TYPE	LOW IRON TEMPERED GLASS 3.2mm	LOW IRON TEMPERED GLASS 3.2mm	LOW IRON TEMPERED GLASS 3.2mm	LOW IRON TEMPERED GLASS 3.2mm
GLASS SEELING	BLACK SILICONE AND DOUBLE ADHENSIVE TAPE			
TESTING PRESSURE	10bar	10bar	10bar	10bar
APPLY FOR	CLOSE CIRCUIT SYSTEM	CLOSE CIRCUIT SYSTEM	CLOSE CIRCUIT SYSTEM	CLOSE CIRCUIT SYSTEM