

HIGH PRESSURE VERTICAL COPPER CYLINDERS (FOR BOILER ROOMS)

MODEL	EL 200P	EL 250P	EL 300P	EL 350P	EL 500P	EL 750P	EL 1000P
CAPACITY (LT)	196	245	293	341	530	760	985
OUTER DIAMETER (cm)	59	59	59	59	90	90	90
OUTER LENGTH (cm)	125	157	185	215	130	170	225
OUTER COVER	PREPAINTED SHEET OR ANODIZED ALUMINIUM	PREPAINTED SHEET OR ANODIZED ALUMINIUM	PREPAINTED SHEET OR ANODIZED ALUMINIUM	PREPAINTED SHEET OR ANODIZED ALUMINIUM	PREPAINTED SHEET OR ANODIZED ALUMINIUM	PREPAINTED SHEET OR ANODIZED ALUMINIUM	PREPAINTED SHEET OR ANODIZED ALUMINIUM
SIDE COVER	PREPAINTED SHEET OR ANODIZED ALUMINIUM	PREPAINTED SHEET OR ANODIZED ALUMINIUM	PREPAINTED SHEET OR ANODIZED ALUMINIUM	PREPAINTED SHEET OR ANODIZED ALUMINIUM	PLASTIC CAPS	PLASTIC CAPS	PLASTIC CAPS
HIGH DENSITY POLYURETHANE INSULATION THICKNESS	65mm	65mm	65mm	65mm	100mm	100mm	100mm
STORAGE TANK MAIN BODY	COPPER SHEET 1.7mm	COPPER SHEET 1.9mm	COPPER SHEET 1.9mm	COPPER SHEET 1.9mm	COPPER SHEET 3mm	COPPER SHEET 3mm	COPPER SHEET 3mm
STORAGE TANK SIDE CIRCLES	COPPER CIRCLES 1.9mm	COPPER CIRCLES 1.9mm	COPPER CIRCLES 1.9mm	COPPER CIRCLES 1.9mm	COPPER CIRCLES 4mm	COPPER CIRCLES 4mm	COPPER CIRCLES 4mm
STORAGE TANK DIAMETER (cm)	46	46	46	46	80	80	80
STORAGE TANK LENGTH	118	147	176	205	115	155	210
INPUT - OUTPUT CONNECTIONS	3/4 COPPER MALE PIPES	3/4 COPPER MALE PIPES	3/4 COPPER MALE PIPES	3/4 COPPER MALE PIPES	1-1½' COPPER FEMALE PIPES	1-1½' COPPER FEMALE PIPES	1-1½' COPPER FEMALE PIPES
ELECTRICAL RESISTANCE	3kw	3kw	3kw	3kw	OPTIONAL 3-6kw	OPTIONAL 3-6kw	OPTIONAL 3-6kw
TESTING PRESSURE (bar)	10	10	10	10	15	15	15
GROSS WEIGHT (kg)	57	66	72	79	155	195	240
CENTRAL HEATING HEAT EXCHANGER LENGTH (cm)	500	750	1000	1000	Φ22-1800	Φ22-1800	Φ22-1800
CENTRAL HEATING HEAT EXCHANGER WEIGHT (kg)	0.700	1,050	1,400	1,400	12	12	12