

HIGH PRESSURE CYLINDERS

MODEL	EL 90P	EL 130P	EL 160P	EL 200P	EL 250P	EL 300P	EL 350P
CAPACITY (LT)	91	131	158	196	245	293	341
OUTER DIAMETER (cm)	50	59	59	59	59	59	59
OUTER LENGTH (cm)	90	95	105	125	157	185	215
OUTER COVER	PREPAINTED SHEET OR ANODIZED ALUMINIUM	PREPAINTED SHEET OR ANODIZED ALUMINIUM	PREPAINTED SHEET OR ANODIZED ALUMINIUM	PREPAINTED SHEET OR ANODIZED ALUMINIUM	PREPAINTED SHEET OR ANODIZED ALUMINIUM	PREPAINTED SHEET OR ANODIZED ALUMINIUM	PREPAINTED SHEET OR ANODIZED ALUMINIUM
SIDE COVER	PREPAINTED SHEET OR ANODIZED ALUMINIUM	PREPAINTED SHEET OR ANODIZED ALUMINIUM	PREPAINTED SHEET OR ANODIZED ALUMINIUM	PREPAINTED SHEET OR ANODIZED ALUMINIUM	PREPAINTED SHEET OR ANODIZED ALUMINIUM	PREPAINTED SHEET OR ANODIZED ALUMINIUM	PREPAINTED SHEET OR ANODIZED ALUMINIUM
HIGH DENSITY POLYURETHANE INSULATION THICKNESS	65mm	65mm	65mm	65mm	65mm	65mm	65mm
STORAGE TANK MAIN BODY	COPPER SHEET 1.5mm	COPPER SHEET 1.6mm	COPPER SHEET 1.7mm	COPPER SHEET 1.7mm	COPPER SHEET 1.9mm	COPPER SHEET 1.9mm	COPPER SHEET 1.9mm
STORAGE TANK SIDE CIRCLES	COPPER CIRCLES 1.5mm	COPPER CIRCLES 1.9mm	COPPER CIRCLES 1.9mm	COPPER CIRCLES 1.9mm	COPPER CIRCLES 1.9mm	COPPER CIRCLES 1.9mm	COPPER CIRCLES 1.9mm
STORAGE TANK DIAMETER (cm)	37	46	46	46	46	46	46
STORAGE TANK LENGTH	80	80	95	118	147	176	205
INPUT - OUTPUT COLLECTOR CONNECTIONS	3/4 COPPER MALE PIPES	3/4 COPPER MALE PIPES	3/4 COPPER MALE PIPES	3/4 COPPER MALE PIPES	3/4 COPPER MALE PIPES	3/4 COPPER MALE PIPES	3/4 COPPER MALE PIPES
ELECTRICAL RESISTANCE	3kw	3kw	3kw	3kw	3kw	3kw	3kw
TESTING PRESSURE (bar)	10	10	10	10	10	10	10
WEIGHT (kg)	29.3	42	49	57	66	72	79
FOR CLOSE CIRCUIT SYSTEMS (DOUBLE WALL HEAT EXCHANGER LENGTH (cm))	32	32	65	75	95	100	130
DOUBLE WALL HEAT EXCHANGER WEIGHT (kg)	2.9	2.9	5.8	6.75	8.6	9	11.7
CENTRAL HEATING HEAT EXCHANGER LENGTH (cm))	250	500	500	500	750	1000	1000
CENTRAL HEATING HEAT EXCHANGER WEIGHT (kg))	0.350	0.700	0.700	0.700	1.050	1.400	1.400