

LOW PRESSURE CYLINDERS

MODEL	EL 90G	EL 130G	EL 155G	EL 200G	EL 250G	EL 300G	EL 350G
CAPACITY (LT)	90	127	154	194	250	293	350
OUTER DIAMETER	45	59	59	59	59	59	59
OUTER LENGTH	90	85	94	116	148	172	207
OUTER COVER	PREPAINTED SHEET OR ANODIZED ALUMINIUM	PREPAINTED SHEET OR ANODIZED ALUMINIUM	PREPAINTED SHEET OR ANODIZED ALUMINIUM	PREPAINTED SHEET OR ANODIZED ALUMINIUM	PREPAINTED SHEET OR ANODIZED ALUMINIUM	PREPAINTED SHEET OR ANODIZED ALUMINIUM	PREPAINTED SHEET OR ANODIZED ALUMINIUM
SIDE COVER	PREPAINTED SHEET OR ANODIZED ALUMINIUM	PREPAINTED SHEET OR ANODIZED ALUMINIUM	PREPAINTED SHEET OR ANODIZED ALUMINIUM	PREPAINTED SHEET OR ANODIZED ALUMINIUM	PREPAINTED SHEET OR ANODIZED ALUMINIUM	PREPAINTED SHEET OR ANODIZED ALUMINIUM	PREPAINTED SHEET OR ANODIZED ALUMINIUM
HIGH DENSITY POLYURETHANE INSULATION THICKNESS	35mm	55mm	55mm	55mm	55mm	55mm	55mm
STORAGE TANK MAIN BODY	COPPER SHEET 0.65mm	COPPER SHEET 0.65mm	COPPER SHEET 0.65mm	COPPER SHEET 0.65mm	COPPER SHEET 0.65mm	COPPER SHEET 0.65mm	COPPER SHEET 0.65mm
STORAGE TANK SIDE CIRCLES	COPPER CIRCLES 1mm	COPPER CIRCLES 1mm	COPPER CIRCLES 1mm	COPPER CIRCLES 1mm	COPPER CIRCLES 1mm	COPPER CIRCLES 1mm	COPPER CIRCLES 1mm
STORAGE TANK DIAMETER (cm)	38	48	48	48	48	48	48
STORAGE TANK LENGTH	80	75	85	107	138	162	197
INPUT - OUTPUT COLLECTOR CONNECTIONS	3/4 COPPER MALE PIPES	3/4 COPPER MALE PIPES	3/4 COPPER MALE PIPES	3/4 COPPER MALE PIPES	3/4 COPPER MALE PIPES	3/4 COPPER MALE PIPES	3/4 COPPER MALE PIPES
ELECTRICAL RESISTANCE	3kw	3kw	3kw	3kw	3kw	3kw	3kw
TESTING PRESSURE	1bar	1bar	1bar	1bar	1bar	1bar	1bar
WEIGHT (kg)	20	30	34.3	40	46	52	59
FOR CLOSE CIRCUIT SYSTEMS (DOUBLE WALL HEAT EXCHANGER LENGTH (cm))	32	32	65	75	95	100	130
DOUBLE WALL HEAT EXCHANGER WEIGHT (kg))	2.9	2.9	5.8	6.75	8.6	9	11.7
CENTRAL HEATING HEAT EXCHANGER LENGTH (cm))	250	500	500	500	750	1000	1000